

## Product Description

### PowerWalker VFI 2000 LCD

- High efficiency results in energy saving with output power factor 0.9
- Emergency Power Off connection and Intelligent Slot for extension card (i.e. SNMP or Modbus)
- Programmable outlets



Item Number: 10120114



With true double-conversion online UPS design, PowerWalker VFI LCD provides powerful and overall protection to your sensitive devices. It can accept wide input voltage for harsh environment. It offers full protection for critical devices such as sensitive servers, network/telephone communication systems as well as for industrial applications.

## Technical specification









General features	
Type	Online
Power capacity	2000VA / 1800W
Output Power Factor	0.90
Input	
Input Voltage Range	Voltage Range Low Line Transfer 110-160VAC ± 5% depending on load level Voltage Range Low Line Comeback 125-175VAC ± 5% depending on load level Voltage Range High Line Transfer 300VAC ± 5% Voltage Range High Line Comeback 290VAC ± 5VAC
Input PF	≥ 0.99 at full load
Frequency Range	40Hz - 70Hz
Frequency (Synchronized Range)	47Hz - 53Hz or 57Hz - 63Hz
Output	
Nominal Output Voltage	208/220/230/240 VAC
Pure Sine Wave	Yes
THDv	≤2% Full Linear Load; ≤4% Non-Linear Load
Voltage Regulation (Bat. Mod.)	±1%
Frequency (Battery Mode)	±0,1Hz
Technical details	
Load Crest Ratio	3:1
Transfer Time [AC to Battery]	0ms
Transfer Time [Inverter to Bypass]	4ms
Generator support	Yes
Overload Capacity	Line: Warning @100%-110%; Bypass @>110%; BAT: Warning @100%-110%; 30s @110%-130%; Shutdown @>130%
External Connection	Battery Yes
Fan Logic	Internal temperature > 50degC: high speed; Inverter NTC temperature > 80degC: high speed; CFCV Mode: high speed; ECO, Bypass, Standby Mode: low speed; Load <60%: low speed; Load 60-80%: half speed; Load > 80%: high speed;
Recharge Time	4h to 90%
Connections and communication	
IEC C13 Outlet	8
Programmable Outlets	Yes
Input	C14
Software	ViewPower
USB port	Yes
RS-232 Port	Yes
Extension Slot	Yes, 1
EPO Port	Yes
RJ-45/RJ-11 protection	Yes
Environment	
Noise Level	< 45dB
Temperature	0°C – 40°C
Humidity	20% - 90% RH (non-condensing)
Logistics	
IEC 62040-3 classification	VFI-SS-111
Package Content	UPS, Manual, Software CD, USB Cable, Input Power Cable, 2x IEC Cable
Manual Languages	EN/DE/FR/ES/RU/IT/PT /TR/PL
EAN	4260074974256
Width	190 mm
Height	318 mm
Depth	421 mm
Weight	26 kg
Giftbox - Width	320 mm
Giftbox - Height	460 mm
Giftbox - Depth	560 mm
Giftbox - Weight	28.5 kg
Pcs. per box	1
Pcs. per layer	4
Pcs. per pal	16

<b>Efficiency</b>	
LINE mode full Load	90.0%
BATTERY mode full Load	88.0%
<b>Batteries and autonomy time</b>	
Batteries	6x 12V/7Ah
DC Voltage	6 x 12V

## Accessories

Name	Product Description	Picture
<p><b><u>SNMP Manager</u></b> Network Management Item Number: 10120505 EAN: 4260074974034</p>	<p>SNMP Cards offer IP Address and Web Interface for most convenient monitoring. SNMP modules allows remote monitor and manage multiple UPSs from anywhere with internet access. Integrated web access will leverage internet capability of SNMP card to remotely program or shut down UPSs. Equipped with SNMP card, power conditions of all UPSs can be monitored anytime/anywhere even through the UPS units are ...</p>	
<p><b><u>SNMP Box</u></b> Network Management Item Number: 10131000 EAN: 4260074977424</p>	<p>SNMP Cards offer IP Address and Web Interface for most convenient monitoring. SNMP modules allows remote monitor and manage multiple UPSs from anywhere with internet access. Integrated web access will leverage internet capability of SNMP card to remotely program or shut down UPSs. Equipped with SNMP card, power conditions of all UPSs can be monitored anytime/anywhere even through the UPS units are ...</p>	
<p><b><u>EMD for SNMP Manager</u></b> Environment Module Item Number: 10120544 EAN: 4260074974966</p>	<p>EMD (environmental monitoring device) for SNMP cards are connectivity devices to remote monitor temperature and humidity via SNMP card. It provides dry contacts to communicate with compatible devices such as security system or alarm system. ...</p>	
<p><b><u>AS400 Card</u></b> Dry Contacts Item Number: 10120515 EAN: 4260074974300</p>	<p>AS/400 Cards provide clean dry contacts for remote shutdown and monitoring of a UPS. It is frequently used along with PLCs and signal control panels. Information delivered are UPS failure, Alarm, Main Fail, Bypass, Battery Low, UPS On. Using AS/400 it possible to shutdown UPS remotely. Solution requires external 12V/24VDC source for a high signal. Pin assignment is available in User ...</p>	
<p><b><u>Modbus Card 2</u></b> Modbus Protocol Item Number: 10120565 EAN: 4260074975703</p>	<p>The PowerWalker Modbus Card is a communication accessory that provides a pair of RJ-45 interface for remote monitoring and controlling of UPSs. It converts standard RS232 signal to RS232 signal with specified address, which allows controlling many UPSs from one computer. You can setup a desired address with jumpers (range 0-255). - Modbus Card for: VFI 1000/1500/2000/3000 LCD VFI 1000C/2000C ...</p>	
<p><b><u>MBS/PDU Tower 1-3kVA</u></b> Maintenance Bypass Switch (Power Distribution Unit) for all 1-3KVA Tower Type UPS Item Number: 10120500 EAN: 4260074973082</p>	<p>MBS is a module used as an external Maintenance Bypass Switch to provide continuous power without shutting down the connected loads during UPS scheduled maintenance or battery replacement. It also serves as a PDU (Power Distribution Unit) offering several outputs to be used by various loads. ...</p>	
<p><b><u>MBS/PDU IEC 1-3kVA</u></b> Maintenance Bypass Switch (Power Distribution Unit) for all 1-3KVA Tower Type UPS Item Number: 10133000 EAN: 4260074978025</p>	<p>MBS is a module used as an external Maintenance Bypass Switch to provide continuous power without shutting down the connected loads during UPS scheduled maintenance or battery replacement. It also serves as a PDU (Power Distribution Unit) offering several outputs to be used by various loads. ...</p>	
<p><b><u>ATS</u></b> Automatic Transfer Switch Item Number: 10120543 EAN: 4260074974959</p>	<p>ATS (Automatic Transfer Switch) supports connection of two independent power sources. If primary power source fails, the secondary will automatically back up the connected load without any interruption. ...</p>	

<p><b>Charger EB72-12A</b> 72VDC, max12A Item Number: 10136003 EAN: 4260074978063</p>	<p>External charger in a stand-alone housing. Works parallel to the UPS. You can connect your battery pack via connector (6x12VDC). Charger has adjustable current. ...</p>	
<p><b>USB Cable</b> USB Cable Item Number: 91010011</p>	<p>Additional communication cable ...</p>	
<p><b>RS-232 Cable</b> RS-232 Cable Item Number: 91010012</p>	<p>Additional communication cable ...</p>	
<p><b>IEC Cable 10A C13/C14 (180cm) 0.75mm<sup>2</sup></b> Extension Cable Item Number: 91010013 EAN: 4260074976274</p>	<p>Additional converter cable ...</p>	
<p><b>EU Input Power Cable C13</b> EU-Input Cable Item Number: 91010017 EAN: 4260074976465</p>	<p>Additional converter cable ...</p>	
<p><b>EU Input Power Cable C19</b> EU-Input Cable Item Number: 91010018 EAN: 4260074976458</p>	<p>Additional converter cable ...</p>	
<p><b>IEC Cable 16A C19/C20 (180cm)</b> Extension Cable Item Number: 91010028 EAN: 4260074976090</p>	<p>Additional converter cable ...</p>	
<p><b>UK Input Power Cable C13 (180cm)</b> UK-Input Cable Item Number: 91010029 EAN: 4260074975826</p>	<p>Additional converter cable ...</p>	
<p><b>UK Input Power Cable C19 (180cm)</b> UK-Input Cable Item Number: 91010030 EAN: 4260074975833</p>	<p>Additional converter cable ...</p>	
<p><b>EU Plug to UK Plug Converter</b> Converter Item Number: 91010031</p>	<p>Additional converter cable ...</p>	
<p><b>IEC Cable 10A C14/C19 (180cm)</b> Extension Cable Item Number: 91010040 EAN: 4260074976182</p>	<p>Additional converter cable ...</p>	
<p><b>IEC Cable 10A C13/C20 (180cm)</b> Extension Cable Item Number: 91010041 EAN: 4260074975710</p>	<p>Additional converter cable ...</p>	
<p><b>IEC Cable 10A C14/TypeF Converter (20cm)</b> Converter Item Number: 91015003 EAN: 7340004644842</p>	<p>Converter cable from IEC C14 to Type F (CEE7/3). 20cm with 3x0.75mm<sup>2</sup> wires ...</p>	
<p><b>Swiss Input Power Cable C13</b> Swiss-Input Cable Item Number: 91015011</p>	<p>Additional converter cable ...</p>	

<p><b>Swiss Input Power Cable C19</b> Swiss-Input Cable Item Number: 91015012</p>	<p>Additional converter cable ...</p>	
<p><b>BP A72T-6x9Ah</b> for VFI 2000/3000 LCD (6x9Ah, 72VDC) Item Number: 10120511 EAN: 4260074974225</p>	<p>Battery Pack for VFI 2000/3000 LCD (6x9Ah, 72VDC). Includes 1 string of 6 batteries, each 12V/9Ah capacity. Battery pack operates on 72VDC nominal voltage. Dimensions are H:220mm x W:145mm x D:397mm. Weight: 20kg. ...</p>	
<p><b>BP A72T-12x9Ah</b> for VFI 2000/3000 LCD (12x9Ah, 72VDC) Item Number: 10120575 EAN: 4260074975932</p>	<p>Battery Pack for VFI 2000/3000 LCD (12x9Ah, 72VDC). Includes 2 strings of 6 batteries, each 12V/9Ah capacity. Battery pack operates on 72VDC nominal voltage. Dimensions are H:318mm x W:190mm x D:421mm. Weight: 40kg. ...</p>	
<p><b>BP A72T-18x9Ah+3A</b> for VFI 2000/3000 LCD (18x9Ah, 72VDC) Item Number: 10120585 EAN: 4260074976267</p>	<p>Battery Pack for VFI 2000/3000 LCD (18x9Ah, 72VDC). Includes 3 strings of 6 batteries, each 12V/9Ah capacity. Battery pack operates on 72VDC nominal voltage. Dimensions are H:318mm x W:190mm x D:535mm. Weight: 67,5kg. Battery pack is additionally equipped with 3A charger. ...</p>	
<p><b>BPH A72T-6</b> for VFI 2000/3000 LCD (for 6bat, 72VDC) Item Number: 10120576 EAN: 4260074976106</p>	<p>Empty Battery Pack fits inside 6pcs. 7Ah / 9Ah ...</p>	
<p><b>BPH A72T-12</b> for VFI 2000/3000 LCD (for 12bat, 72VDC) Item Number: 10120577 EAN: 4260074976113</p>	<p>Empty Battery Pack fits inside 12pcs. 7Ah / 9Ah ...</p>	
<p><b>BPH A72T-18+3A</b> for VFI 2000/3000LCD(for 18bat, 72VDC)3A Item Number: 10120578 EAN: 4260074976120</p>	<p>Empty Battery Pack fits inside 18pcs. 7Ah / 9Ah / 3A charger ...</p>	
<p><b>PWB12-7</b> PowerWalker 7Ah Battery Item Number: 91010090 EAN: 4260074978131</p>	<p>PowerWalker PWB12 battery series is designed to work with UPS solutions. It is a high quality valve-regulated lead acid battery with high corrosion resistance and special exhaust structure. The sealing technology with high discharge capacity offers long life, reliability and safety. Batteries are flexible for installation and maintenance and easy to handle.  Design life is 3-5 years. The bat ...</p>	

**PWB12-9**

PowerWalker 9Ah Battery

Item Number: 91010091

EAN: 4260074978148

PowerWalker PWB12 battery series is designed to work with UPS solutions. It is a high quality valve-regulated lead acid battery with high corrosion resistance and special exhaust structure. The sealing technology with high discharge capacity offers long life, reliability and safety. Batteries are flexible for installation and maintenance and easy to handle.

Design life is 3-5 years. The bat ...

